

SAFETY DATA SHEET

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

Product Name and/or Code: **NOROX 750**

Intended use: Initiator for unsaturated polyester resin.


Name and address of the company: Syrgis Performance Initiators AB
Box 26083
SE-100 41 Stockholm
Sweden

Telephone: +46 8 545 121 60

In case of an emergency: contact tel. +46 8 33 70 43 or National Poison Centre.

2. HAZARDS IDENTIFICATION OF THE PREPARATION

Danger classification: O = Oxidising
C = Corrosive



May cause fire. Causes burns. Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in aquatic environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	EINECS-no	CAS-no	Conc. %	Symbol/R-phrases
Cumyl hydroperoxide	201-254-7	80-15-9	14-16	O, T, N / 7-21/22-23-34-48/20/22-51/53
Acetyl acetone peroxide	204-626-7	37187-22-7	25-30	Xi / 5-8-36/38
Proprietary phlegmatizer	212-828-1	872-50-4	45-50	Xi / 36/38
Cumene	202-704-5	98-82-8	2-3	Xi, N / 10-37-51/53-65
Hydrogen peroxide	231-765-0	7722-84-1	< 1	O, C / 5, 8, 20/22, 35
Water			< 4	none

For the full R-phrases see section 16.

4. FIRST AID MEASURES

General:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation:

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

Skin contact:

Remove contaminated clothing. Wash skin thoroughly with soap and water. Treat the contaminated parts like burns. Seek medical advice if necessary.

Eye contact:

Irrigate copiously with clean, fresh water for at least 15 minutes apart and seek medical advice if necessary.

Ingestion:

If accidentally swallowed obtain immediate medical attention. **Do not induce vomiting.** Under medical attention: if the injured person is conscious, make him drink water and charcoal tablets in addition; if the injured person is unconscious or has convulsions, keep him in a warm place while waiting for the physician's advice.

5. FIRE-FIGHTING MEASURES

Flash point: > 65 °C

Autoignition point: Not applicable

Fire-fighting: Water from a safe distance – preferably with a fog nozzle. In case of small fires, other means such as carbon dioxide, foam or dry chemical extinguishers may be effective. In case of fire near storage area, cool the containers with water spray.

Combustion and decomposition products, see section 10.

6. ACCIDENTAL RELEASE MEASURES

Avoid sources of ignition and ventilate the area. Absorb the leak with an inert, non-combustible absorbent material, e.g. sand, earth, perlite or vermiculite. Transfer the material into a clean approved container for proper disposal. Wet the material with water. Wash the contaminated zone. Dike to prevent runoff from entering drains, sewers, streams etc. Avoid skin and eye contact. Wear personal protection equipment recommended in section 8.

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Handling:

Provide adequate ventilation. Keep containers tightly closed when not in use. Do not use near food or drink. Avoid skin and eye contact. Avoid breathing vapours. Wear personal protection equipment recommended in section 8. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Dilution is not recommended. Never dilute with acetone.

Storage:

Store in accordance with local regulations. Store in original package, in cool, well ventilated place away from sources of heat, fires, sparks and direct sunlight. For maximum shelf life we recommend to store the product at temperatures not higher than 25°C. At higher temperatures the shelf life will be reduced. For safety reasons the storage temperature should not exceed 35°C. The product should not be stored below 0°C. The product must never be stored together with accelerators such as dryers, heavy metal compounds etc. Avoid contact with rust. Keep away from sources of ignition. Keep away from oxidising agents, from strongly alkaline and strongly acid materials. Rotate stock using the oldest material first. Prevent unauthorised access.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Measures.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use clean equipment and tools of inert material such as stainless steel, polyethylene, polypropylene, glass. All equipment should be earthed. Use Peleus ball when pipetting the peroxide solutions.

Exposure Limits:

Component	CAS-no.	Swedish Exp.limits / Type	ACGIH / Type
Cumene	98-82-8	25 ppm / TLV	50 ppm / TLV

No EEC-list available.

TLV = Threshold Limited Value

Personal Protection.

Respiratory protection:

Is required if the limit like TLV is exceeded. Gasmask and self-protector according to the concentration presented in atmosphere.

Hand protection:

Use resistant gloves of: butylrubber, ethylen-vinylalcohol, teflon.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection:

Use safety eyewear designed to protect against splash of liquids. Splashes in the eyes may cause serious eye damage.

Skin protection:

Personnel should wear antistatic clothing made of natural fibre or of high temperature resistant synthetic fibre. All parts of the body should be washed after contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Active oxygen %	5.1 - 5.4
Flash point (°C)	> 65
Vapour density (Air=1)	Heavier than Air
L.E.L. (%)	N/A
Odour	slight odour
Colour	light yellow
Viscosity at 20°C (mPas)	13 – 16
Density at 20°C (g/cm³)	1.07 – 1.10
Boiling point	Not determined

10. STABILITY AND REACTIVITY**Stability:**

Comparatively stable at ambient temperature. SADT: above 80°C

Hazardous reactions:

Self-decomposition is catalysed by substances such as acids, strong bases, tert-amines, Friedel-Crafts catalysts and heavy metals.

Materials and conditions to avoid:

Violent reactions can occur if the product comes in contact with cobalt accelerators or other peroxide accelerators /promoters, rust, heavy metal compounds, brass, galvanized steel, acetone, reducing or oxidizing agents and strong acids or bases. Therefore these materials must be avoided. Grinding dust and dirt must be avoided as well. Avoid higher temperatures and direct sunlight. Confinement in stainless steel equipments (tanks, vessels, pipes etc) must also be avoided.

Combustion and decomposition products:

Acetophenone, acetone, phenol, dimethylphenylcarbinol, CO_x.

11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself.

LD50 (oral-rat): 382 mg/kg (CHP); 1400 mg/kg (Cumene)
LD50 (skin-rat): 500 mg/kg (CHP)
LC50 (inh.-rat): 220 ppm/4h (CHP); 8000 ppm/4h (Cumene)

Toxicity effects:

This product is extremely irritant for the eyes, just a few drops of it might cause irreversible lesion and permanent injury of the cornea. If there is a skin contact, it might cause irritation, skin-rash, swelling and chapping. The inhalation of its vapours causes cough, headache and irritation of the respiratory-system. Its

swallowing causes strong irritation and burn of throat and stomach. Perforations of the mucous membranes might occur and, according to its quantity, it might also cause the death of the injured person. The organic peroxides are dangerous for the organism since the peroxide oxygen is reduced to radical that induces into the cellular metabolism.

Skin contact:

Strongly irritant. Causes burns

Eyes contact:

Strongly irritant, corrosive.

Inhalation:

Harmful

Cancerogenic-Mutagenic-Reproductive effects:

No evidence of these effects has been reported.

12. ECOLOGICAL INFORMATION

There are no data available on the preparation itself.
The product should not be allowed to enter drains of water courses.

Biodegradability(Cumyl hydroperoxide)

17% (DOC; modif. OECD screening test / OECD 301E)

Aquatic toxicity(Cumyl hydroperoxide)

Toxicity to fish(<i>Leuciscus idus melanotus</i>):	LC 50: 17mg/l 48h	(DIN 38412, part 15)
Toxicity to bacteria(<i>Pseudomonas putida</i>):	EC 10: 103 µl/l 18h	(Bringmann-Kühn test)

This product is not easily biodegradable. It's harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses. Water and emptied containers should be handled according to local regulations.

The producer recommends destruction of both peroxide rests and empty packaging by combustion under controlled forms.


14. TRANSPORT INFORMATION

Proper Shipping Name: Organic peroxide type D, liquid (acetyl acetone peroxide)	
UN 3105	Class: 5.2
	Label: 5.2
	Packaging group: II
Marine pollutant: No	EmS: F-J, S-R

15. REGULATORY INFORMATION



O



C

Danger classification: O = Oxidising
C = Corrosive

Contains: Acetyl acetone peroxide
Cumyl hydroperoxide

R phrases:

R-7 May cause fire.

R-34 Causes burns.

R-48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in aquatic environment.

S phrases:

S-3/7 Keep container tightly closed in a cool place.

S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S-36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S-45 In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible)

S-50 Do not mix with accelerators, reducing agents, strong acids, alkalis and heavy metal compounds.

S-61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

16. OTHER INFORMATION

In addition from section 2:

Cumyl hydroperoxide. Symbol O, T, N

- R-7 May cause fire.
- R-21/22 Harmful in contact with skin and if swallowed.
- R-23 Toxic by inhalation.
- R-34 Causes burns.
- R-48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
- R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environment.

Cumene. Symbol Xi, N.

- R-10 Flammable
- R-37 Irritating to respiratory system
- R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in aquatic environment.
- R-65 Hazard. May cause lung damage if swallowed.

Acetyl acetone peroxide. Symbol Xi.

- R-5 Heating may cause an explosion
- R-8 Contact with combustible material may cause fire
- R-36/38 Irritating to eyes and skin

Hydrogen peroxide. Symbol C, O

- R-5 Heating may cause an explosion
- R-8 Contact with combustible material may cause fire
- R-20/22 Harmful by inhalation and if swallowed
- R-34 Causes severe burns

Proprietary phlegmatizer. Symbol Xi.

- R-36/38 Irritating to eyes and skin

This product is produced in Sweden.